

IN THE CLAIMS:

The text of all pending claims, (including withdrawn claims) is set forth below. Cancelled and not entered claims are indicated with claim number and status only. The claims as listed below show added text with underlining and deleted text with ~~striketrough~~. The status of each claim is indicated with one of (original), (currently amended), (cancelled), (withdrawn), (new), (previously presented), or (not entered).

1-10. (Cancelled)

11. (Previously Presented) A method for estimating the position of a subscriber station in a radio communication system, comprising:

receiving reports from the subscriber station at a receive station, each report containing information relating to a signal strength at a location of the subscriber station of at least one receive signal received by the subscriber station and sent by a transmitting station;

storing the reports in a memory of a network device of the radio communication system;
receiving a request for position estimation at the radio communication system; and
estimating the position at a position determining unit taking into account at least two reports stored prior to the request for position estimation.

12. (Previously Presented) The method according to claim 11, wherein the receive station is used as the network device.

13. (Previously Presented) The method according to claim 11, wherein the reports are received and/or stored regularly at specific time intervals.

14. (Previously Presented) The method according to claim 11, wherein the reports are received and stored regularly at specific time intervals, and the reports are received and stored during both an active connection and in an idle mode.

15. (Previously Presented) The method according to claim 11, wherein the memory stores a first number of reports as a maximum.

16. (Previously Presented) The method according to claim 11, wherein the

position determining unit requests a second number of reports from the network device.

17. (Previously Presented) The method according to claim 16, wherein
if the number of reports stored is fewer than the second number when the request for
position estimation is received, then the network device stores additional reports until the second
number of reports has been stored or until a maximum period of time has expired,
if the second number of reports is stored before expiration of the maximum period of
time, then the network device sends the second number of reports prior to the expiry of the
maximum period of time, and
if the second number of reports cannot be stored before expiration of the maximum
period of time, then the base station sends all stored reports after the expiry of the maximum
period of time, even if the number of stored reports remains smaller than the second number of
reports.

18. (Previously Presented) The method according to claim 11, wherein the
position determining unit estimates position by comparing signal strengths obtained from the
reports with signal strengths stored in a signal strength database.

19. (Previously Presented) The method according to claim 11, wherein each
report also contains information relating to a transmitting power used to transmit the at least one
receive signal.

20. (Previously Presented) The method according to claim 11, wherein the
reports also contain:
a transmitting power used by the subscriber station to transmit the report to the receive
station, and
a receive power at which each report was received by the receive station in each case].

21. (Previously Presented) The method according to claim 12, wherein
the reports are received and stored regularly at specific time intervals, and
the reports are received and stored during both an active connection and in an idle
mode.

22. (Previously Presented) The method according to claim 21, wherein

the memory stores a first number of reports as a maximum.

23. (Previously Presented) The method according to claim 22, wherein the position determining unit requests a second number of reports from the network device.

24. (Previously Presented) The method according to claim 23, wherein if the number of reports stored is fewer than the second number when the request for position estimation is received, then the network device stores additional reports until the second number of reports has been stored or until a maximum period of time has expired,

if the second number of reports is stored before expiration of the maximum period of time, then the network device sends the second number of reports prior to the expiry of the maximum period of time, and

if the second number of reports cannot be stored before expiration of the maximum period of time, then the base station sends all stored reports after the expiry of the maximum period of time, even if the number of stored reports remains smaller than the second number of reports.

25. (Previously Presented) The method according to claim 24, wherein the position determining unit estimates position by comparing signal strengths obtained from the reports with signal strengths stored in a signal strength database.

26. (Previously Presented) The method according to claim 25, wherein each report also contains information relating to a transmitting power used to transmit the at least one receive signal.

27. (Previously Presented) The method according to claim 26, wherein the reports also contain:

a transmitting power used by the subscriber station to transmit the report to the receive station, and

a receive power at which each report was received by the receive station in each case].

28. (Previously Presented) A network device for a radio communication system, comprising:

a memory for storing the reports, which a receive station has received from a subscriber

station, in which the reports in each case contain information relating to a signal strength at a location of the subscriber station of at least one receive signal received by the subscriber station and sent by a transmitting station;

a transmitter to transmit, after a request for position estimation has been received at the radio communication system, at least two reports stored prior to receiving the request for position estimation, the reports being transmitted to a position determining unit, in which the position is estimated taking into account the at least two reports; and

a controller to control the network device so that at least two reports are stored prior to the request for position estimation.